NSN 4720-01-414-0416

Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-01-414-0416

Cross Sectional Shape:
Round
Inside Diameter:
0.500 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
1.250 inches
Minimum Inside Bending Radius:
8.000 inches
Exterior Color:
Black
Quick Disconnect Size:
0.625 inches 1st end
Connection Style:
Cam (external) 1st end
Connection Type:
Universal quick disconnect 1st end
Burst Test Pressure:
2000.0 pounds per square inch
Layer Composition And Location:
1st layer braided steel wire and 2nd layer braided steel wire and 3rd layer braided steel wire and 4th layer braided steel wire and 5th layer
braided steel wire and 6th layer braided steel wire and outer layer molded rubber, synthetic
Maximum Operating Pressure:
500.0 pounds per square inch
Hydrostatic Test Pressure:
1000.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
600.000 inches
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A542a0