NSN 4720-01-414-2297

Cross Sectional Shape:

Round

Thread Class:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-414-2297

3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Diameter:
0.375 inches
Minimum Inside Bending Radius:
4.000 inches
Angle Between Rigid Elbow Fittings In Deg:
270.0
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Elbow 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Burst Test Pressure:
10000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
3000.0 pounds per square inch
Flow Angle:
90.0 degrees 1st end
Vacuum In Torr:
50.8
Inside Surface Condition:
Smooth

NSN 4720-01-414-2297

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Me	thod And	Length:
12.625 inches	working	

Thread Series Designator:

Unjf 1st end

Specification Data:

96906-ms8000 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0