## NSN 4720-01-414-5577

**Cross Sectional Shape:** 

Round

Thread Class: 2b 1st end

Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches

**Tempurature Rating:** 

Metallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-414-5577

1500.0 degrees fahrenheit single response
Outside Diameter:
0.535 inches
Minimum Inside Bending Radius:
4.000 inches
Inner Conveying Tube Style:
Annular close-pitch corrugated
End Application:
Loader, scoop type; ded 4/4 w/4 1-1/2 or 5 cy gp
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Identical ends
Burst Test Pressure:
8000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
2000.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
4000.0 pounds per square inch
Measuring Method And Length:
72.000 inches working
Thread Series Designator:
Unf 1st end

## NSN 4720-01-414-5577

Metallic Hose Assembly - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0