

View Online at <https://aerobasegroup.com/nsn/4720-01-414-5579>

**Cross Sectional Shape:**

Round

**Inside Diameter:**

0.500 inches

**Temperature Rating:**

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

**Outside Diameter:**

1.250 inches

**Minimum Inside Bending Radius:**

8.000 inches

**Exterior Color:**

Black

**Quick Disconnect Size:**

0.625 inches 1st end

**Connection Style:**

Cam (external) 1st end

**Connection Type:**

Universal quick disconnect 1st end

**Burst Test Pressure:**

2000.0 pounds per square inch

**Layer Composition And Location:**

1st layer braided steel wire and 2nd layer braided steel wire and 3rd layer braided steel wire and 4th layer braided steel wire and 5th layer braided steel wire and 6th layer braided steel wire and outer layer molded rubber, synthetic

**Maximum Operating Pressure:**

500.0 pounds per square inch

**Hydrostatic Test Pressure:**

1000.0 pounds per square inch

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

60.000 inches

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0