Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-01-414-5582

Cross Sectional Shape:

Round

Inside Diameter:

0.500 inches

Tempurature Rating:

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Outside Diameter:

1.250 inches

Minimum Inside Bending Radius:

8.000 inches

Exterior Color:

Black

Quick Disconnect Size:

0.625 inches 1st end

Connection Style:

Cam (external) 1st end

Connection Type:

Universal quick disconnect 1st end

Burst Test Pressure:

2000.0 pounds per square inch

Layer Composition And Location:

1st layer braided steel wire and 2nd layer braided steel wire and 3rd layer braided steel wire and 4th layer braided steel wire and 5th layer braided steel wire and 6th layer braided steel wire and outer layer molded rubber, synthetic

Maximum Operating Pressure:

500.0 pounds per square inch

Hydrostatic Test Pressure:

1000.0 pounds per square inch

Inside Surface Condition:

Smooth

Measuring Method And Length:

36.000 inches

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0