

View Online at <https://aerobasegroup.com/nsn/4720-01-414-7856>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.406 inches

Temperature Rating:

-65.0 degrees fahrenheit and 302.0 degrees fahrenheit single response

Outside Diameter:

0.770 inches

Minimum Inside Bending Radius:

1.500 inches

Exterior Color:

Black

End Application:

Wiggins lift. Co. 15k forklift

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded internal tube 1st end

Burst Test Pressure:

2000.0 pounds per square inch

Layer Composition And Location:

1st layer braided polyester cord and 2nd layer braided polyester cord and outer layer braided polyester cord

Maximum Operating Pressure:

500.0 pounds per square inch

Thread Size:

0.750 inches 1st end

Seat Angle:

45.0 degrees 1st end

Hydrostatic Test Pressure:

1000.0 pounds per square inch

Inside Surface Condition:

Smooth

Measuring Method And Length:

24.210 inches

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0