NSN 4720-01-414-7856

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-414-7856

Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.406 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 302.0 degrees fahrenheit single response
Outside Diameter:
0.770 inches
Minimum Inside Bending Radius:
1.500 inches
Exterior Color:
Black
End Application:
Wiggins lift. Co. 15k forklift
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
2000.0 pounds per square inch
Layer Composition And Location:
1st layer braided polyester cord and 2nd layer braided polyester cord and outer layer braided polyester cord
Maximum Operating Pressure:
500.0 pounds per square inch
Thread Size:
0.750 inches 1st end
Seat Angle:
45.0 degrees 1st end
Hydrostatic Test Pressure:
1000.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
24.210 inches
Thread Series Designator:

Unf 1st end

NSN 4720-01-414-7856

Nonmetallic Hose Assembly - Page 2 of 2



		ife:	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0