NSN 4720-01-414-7950

Cross Sectional Shape:

Round

Thread Class: 3b 1st end

Thread Direction: Right-hand 1st end

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-414-7950

Inside Diameter:
Between 0.242 inches and 0.273 inches
Tempurature Rating:
-40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response
Outside Diameter:
0.557 inches
Minimum Inside Bending Radius:
4.000 inches
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
11000.0 pounds per square inch
Maximum Operating Pressure:
2750.0 pounds per square inch
Thread Size:
0.688 inches 2nd end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
5500.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Outer Covering Environmental Protection:
Abrasion resistant and oil resistant and waterproof
Abrasion resistant and oil resistant and waterproof Inside Surface Condition:
· · · · · · · · · · · · · · · · · · ·
Inside Surface Condition:
Inside Surface Condition: Smooth
Inside Surface Condition: Smooth Measuring Method And Length:
Inside Surface Condition: Smooth Measuring Method And Length: 1130.0 millimeters working
Inside Surface Condition: Smooth Measuring Method And Length: 1130.0 millimeters working Media For Which Designed:

NSN 4720-01-414-7950

Nonmetallic Hose Assembly - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0