Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-01-414-9293

| Cross Sectional Shape: | |
|-------------------------------------|---------------------------------------|
| Round | |
| Inside Diameter: | |
| 1.500 inches | |
| Tempurature Rating: | |
| - | .0 degrees fahrenheit single response |
| Outside Diameter: | |
| 2.500 inches | |
| Minimum Inside Bending Radius | 5: |
| 9.000 inches | |
| Angle Between Rigid Elbow Fitti | ngs In Deg: |
| 0.0 | |
| End Application: | |
| W/s code helicopter, super jolly h- | 53 |
| End Connection Design: | |
| Elbow 1st end | |
| Connection Type: | |
| Threaded internal tube 1st end | |
| Burst Test Pressure: | |
| 600.0 pounds per square inch | |
| Layer Composition And Location | n: |
| 1st layer braided polyester cord an | d outer layer braided polyester cord |
| Maximum Operating Pressure: | |
| 100.0 pounds per square inch | |
| Hydrostatic Test Pressure: | |
| 300.0 pounds per square inch | |
| Flow Angle: | |
| 45.0 degrees 1st end | |
| Inside Surface Condition: | |
| Smooth | |
| Measuring Method And Length: | |
| 33.000 inches working | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A542a0 | |