NSN 4720-01-415-4313

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-415-4313

Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.750 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response
Outside Diameter:
1.250 inches
Minimum Inside Bending Radius:
5.000 inches
End Application:
2350-01-390-4683
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
12 2nd end
Layer Composition And Location:
1st layer braided textile yarn and 2nd layer helix wire coil and 3rd layer braided textile yarn and outer layer molded rubber, synthetic
Maximum Operating Pressure:
300.0 pounds per square inch
Thread Size:
1.062 inches 2nd end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
600.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
180.000 inches working
Special Features:
Hose assembly includes 1 plug assembly, 1 cap assembly, and 2 retainers

Fuel/oil, hydrocarbon single response

Media For Which Designed:

NSN 4720-01-415-4313

Nonmetallic Hose Assembly - Page 2 of 2



Thread	Series	Design	nator:
	0000	_00.9.	

Un 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0