NSN 4720-01-415-4313

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-415-4313

| Cross Sectional Shape: |
|--|
| Round |
| Thread Class: |
| 2b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.750 inches |
| Tempurature Rating: |
| -40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response |
| Outside Diameter: |
| 1.250 inches |
| Minimum Inside Bending Radius: |
| 5.000 inches |
| End Application: |
| 2350-01-390-4683 |
| Connection Style: |
| Swivel nut flare 1st end |
| End Connection Design: |
| Straight 2nd end |
| Connection Type: |
| Threaded internal tube 1st end |
| Thready Qty Per Inch (tpi): |
| 12 2nd end |
| Layer Composition And Location: |
| 1st layer braided textile yarn and 2nd layer helix wire coil and 3rd layer braided textile yarn and outer layer molded rubber, synthetic |
| Maximum Operating Pressure: |
| 300.0 pounds per square inch |
| Thread Size: |
| 1.062 inches 2nd end |
| Seat Angle: |
| 37.0 degrees 2nd end |
| Hydrostatic Test Pressure: |
| 600.0 pounds per square inch |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 180.000 inches working |
| Special Features: |
| Hose assembly includes 1 plug assembly, 1 cap assembly, and 2 retainers |

Fuel/oil, hydrocarbon single response

Media For Which Designed:

NSN 4720-01-415-4313

Nonmetallic Hose Assembly - Page 2 of 2



| Thread | Series | Design | nator: |
|--------|---------------|--------|--------|
| | 0000 | _00.9. | |

Un 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0