NSN 4720-01-415-4428

Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-01-415-4428

| Cross Sectional Shape: |
|--|
| Round |
| Inside Diameter: |
| 0.375 inches |
| Tempurature Rating: |
| -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.750 inches |
| Minimum Inside Bending Radius: |
| 4.000 inches |
| End Application: |
| Motor drive assembly, almon a. Johnson, inc., e332-5187 for towing machine, series 332 |
| Connection Type: |
| Threaded internal tube 1st end |
| Burst Test Pressure: |
| 5000.0 pounds per square inch |
| Layer Composition And Location: |
| 1st layer braided fiber and 2nd layer braided fiber and outer layer molded rubber, chloroprene |
| Maximum Operating Pressure: |
| 1125.0 pounds per square inch |
| Hydrostatic Test Pressure: |
| 2250.0 pounds per square inch |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 28.000 inches |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A542a0 |
| |
| |