Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-01-415-6621

	ctional Shape:
Round	
Inside Dia	imeter:
Between 0	0.188 inches and 0.214 inches
Tempurat	ure Rating:
-40.0 degre	ees fahrenheit and 200.0 degrees fahrenheit single response
Outside D	liameter:
Between 0	0.500 inches and 0.539 inches
Minimum	Inside Bending Radius:
3.000 inch	es
End Appli	cation:
Pendent as	ssembly on arleigh burke class ddg
Connectio	on Type:
Threaded i	internal tube 1st end
Burst Tes	t Pressure:
4000.0 pou	unds per square inch
Layer Con	nposition And Location:
1st layer b	raided textile yarn and 2nd layer braided textile yarn and outer layer molded rubber, synthetic
Maximum	Operating Pressure:
1000.0 pou	unds per square inch
Hydrostat	ic Test Pressure:
2000.0 pot	unds per square inch
Inside Sur	rface Condition:
Smooth	
Measuring	g Method And Length:
120.000 in	ches working
Media For	Which Designed:
Water, fre	sh and water, salt and fuel/oil, hydrocarbon single response
Reference	e Number Differentiating Characteristics:
As differen	ntiated by use
Shelf Life:	:
N/a	
Unit Of Me	easure:
Demilitari	zation:
No	
Fiig:	
A542a0	