NSN 4720-01-416-1563

A542a0

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-416-1563

Cross Sectional Shape:
Round
Inside Diameter:
6.000 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
6.875 inches
Exterior Color:
Black
Quick Disconnect Size:
6.000 inches 2nd end
End Application:
5430-01-374-5656
Connection Style:
Cam or lever (external) 2nd end
End Connection Design:
Straight 2nd end
Connection Type:
Internal quick disconnect 1st end
Burst Test Pressure:
300.0 pounds per square inch
Layer Composition And Location:
1st layer spirally laid cord strands and 2nd layer helix steel coil and outer layer molded rubber, chloroprene
Maximum Operating Pressure:
150.0 pounds per square inch
Outer Covering Environmental Protection:
Oil resistant and ozone resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
120.000 inches
Specification Data:
81349-mil-h-370 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

NSN 4720-01-416-1563

Nonmetallic Hose Assembly - Page 2 of 2



Mil-std (military Standard):

Mil-prf-370 spec.