Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-01-416-3239

cross Sectional Shape:	
Round	
nside Diameter:	
.250 inches	
empurature Rating:	
40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response	
outside Diameter:	
.690 inches	
linimum Inside Bending Radius:	
.000 inches	
Quick Disconnect Size:	
.250 inches 2nd end	
and Application: 350-01-390-4683	
Connection Style:	
Push (internal) 1st end	
ind Connection Design:	
traight 2nd end	
Connection Type:	
nternal quick disconnect 1st end Burst Test Pressure:	
3000.0 pounds per square inch	
ayer Composition And Location:	
st layer braided wire and 2nd layer braided wire and outer layer molded rubbe	, synthetic
Iaximum Operating Pressure:	
300.0 pounds per square inch	
nside Surface Condition:	
smooth	
leasuring Method And Length:	
44.000 inches	
pecial Features:	
ncludes: plug 1, cap 1, bandmarker 5	
ledia For Which Designed:	
uel/oil, hydrocarbon and hydraulic fluid, water base single response	
shelf Life:	
Init Of Measure:	
Demilitarization:	
'es - demil/mli	
iig:	