## NSN 4720-01-416-3239

Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-01-416-3239

Cross Sectional Shape:
Round
Inside Diameter:
0.250 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response
Outside Diameter:
0.690 inches
Minimum Inside Bending Radius:
4.000 inches
Quick Disconnect Size:
0.250 inches 2nd end
End Application:
2350-01-390-4683
Connection Style:
Push (internal) 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Internal quick disconnect 1st end
Burst Test Pressure:
23000.0 pounds per square inch
Layer Composition And Location:
1st layer braided wire and 2nd layer braided wire and outer layer molded rubber, synthetic
Maximum Operating Pressure:
4300.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
144.000 inches
Special Features:
Includes: plug 1, cap 1, bandmarker 5
Media For Which Designed:
Fuel/oil, hydrocarbon and hydraulic fluid, water base single response
Shelf Life:
N/a
Unit Of Measure:
<u>-</u>
Demilitarization:
Yes - demil/mli
Fiig:
A542a0