NSN 4720-01-416-3250

Cross Sectional Shape:

Inside Diameter: 0.750 inches

Tempurature Rating:

Outside Diameter:

Quick Disconnect Size:
0.750 inches 2nd end
End Application:
2350-01-390-4683
Connection Style:
Push (internal) 1st end
End Connection Design:

Minimum Inside Bending Radius:

End Fitting Component And Material:

Fitting Component And Surface Treatment:

Complete fitting steel all ends

1.260 inches

11.000 inches

Straight 2nd end

Round

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-416-3250

-40.0 degrees fahrenheit single response and 250.0 degrees fahrenheit single response

Complete fitting zinc 1st end					
Connection Type:					
Internal quick disconnect 1st end					
Second End Relationship With First End					
Not identical					
Burst Test Pressure:					
25000.0 pounds per square inch					
First End Swivel Action Capability:					
Not included					
Layer Composition And Location:					
1st layer spirally laid steel wire err-100					
Maximum Operating Pressure:					
4300.0 pounds per square inch					
Inside Surface Condition:					
Smooth					
Measuring Method And Length:					
186.000 inches					
Second End Swivel Action Capability:					
Not included					
Special Features:					
Includes: cap 1, plug 1, bandmarker 7					

NSN 4720-01-416-3250

Nonmetallic Hose Assembly - Page 2 of 2



Me	dia	For	Which	Design	ed:

Fuel/oil, hydrocarbon single response and hydraulic fluid, water base single response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0