

View Online at <https://aerobasegroup.com/nsn/4720-01-416-3259>

**Cross Sectional Shape:**

Round

**Thread Class:**

2b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.500 inches

**Temperature Rating:**

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

**Outside Diameter:**

0.908 inches

**Minimum Inside Bending Radius:**

7.000 inches

**End Application:**

2590-01-384-6857

**Connection Style:**

Swivel nut flare 1st end

**End Connection Design:**

Straight 2nd end

**Connection Type:**

Threaded internal tube 1st end

**Burst Test Pressure:**

14000.0 pounds per square inch

**Layer Composition And Location:**

1st layer braided wire and 2nd layer braided wire and outer layer molded rubber, synthetic

**Maximum Operating Pressure:**

3500.0 pounds per square inch

**Thread Size:**

0.750 inches 2nd end

**Seat Angle:**

37.0 degrees 1st end

**Hydrostatic Test Pressure:**

7000.0 pounds per square inch

**Outer Covering Environmental Protection:**

Weatherproof and oil resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

4.500 inches excluding end fittings

**Media For Which Designed:**

Fuel/oil, hydrocarbon and hydraulic fluid, water base single response

**Thread Series Designator:**

Unjf 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0