NSN 4720-01-416-5913

Nonmetallic Hose Assembly - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/4720-01-416-5913 | |
|--|--|
| Cross Sectional Shape: | |
| Round | |
| Thread Class: | |
| 2b 1st end | |
| Thread Direction: | |
| Right-hand 1st end | |
| Inside Diameter: | |
| 0.406 inches | |
| Tempurature Rating: | |
| -100.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response | |
| Outside Diameter: | |
| 0.531 inches | |
| Minimum Inside Bending Radius: | |
| 5.000 inches | |
| Exterior Color: | |
| Black | |
| End Application: | |
| Forklift, 15k, wiggins lift co. | |
| Connection Style: | |
| Swivel nut flare 1st end | |
| End Connection Design: | |
| Straight 1st end | |
| Connection Type: | |
| Threaded internal tube 1st end | |
| Burst Test Pressure: | |
| 8000.0 pounds per square inch | |
| Layer Composition And Location: | |
| Outer layer braided corrosion resistant steel wire | |
| Maximum Operating Pressure: | |
| 2000.0 pounds per square inch | |
| Thread Size: | |

Thread Size:

0.750 inches 1st end **Seat Angle:**

37.0 degrees 1st end

Hydrostatic Test Pressure:

4000.0 pounds per square inch

Inside Surface Condition:

Smooth

Measuring Method And Length:

13.310 inches working

Thread Series Designator:

Unf 1st end

NSN 4720-01-416-5913

Nonmetallic Hose Assembly - Page 2 of 2



| _ | | | | | |
|---|----|------|---|--------|--|
| c | hο | JIF. | | .ife: | |
| J | | | _ | .II C. | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0