

View Online at <https://aerobasegroup.com/nsn/4720-01-416-6749>

Cross Sectional Shape:

Round

Inside Diameter:

Between 30.6 millimeters and 33.0 millimeters

Temperature Rating:

-40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response

Bolt Circle Diameter:

1.375 inches 1st end

Flange Thickness:

0.625 inches 1st end

Outside Diameter:

41.3 millimeters

Minimum Inside Bending Radius:

6.000 inches

Bolt Hole Quantity:

4 1st end

Flange Outside Diameter:

1.750 inches 1st end

End Application:

3930-01-384-5310

Connection Style:

Plain w/ gasket groove (sae flanged head) 1st end

Bolt Hole Diameter:

0.406 inches 1st end

End Flange Construction:

Solid 1st end

End Connection Design:

Elbow 1st end

Connection Type:

Plain face flange 1st end

Burst Test Pressure:

1000.0 pounds per square inch

Layer Composition And Location:

1st layer braided textile yarn and 2nd layer helix wire coil and outer layer molded rubber, synthetic

Maximum Operating Pressure:

250.0 pounds per square inch

Hydrostatic Test Pressure:

500.0 pounds per square inch

Flow Angle:

90.0 degrees 1st end

Outer Covering Environmental Protection:

Oil resistant and ozone resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

955.0 millimeters working

Flange Style:

Round w/ bolt holes 1st end

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0