## NSN 4720-01-416-6749

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4/20-01-416-6/49
Cross Sectional Shape:
Round
Inside Diameter:
Between 30.6 millimeters and 33.0 millimeters
Tempurature Rating:
-40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response
Bolt Circle Diameter:
1.375 inches 1st end
Flange Thickness:
0.625 inches 1st end
Outside Diameter:
41.3 millimeters
Minimum Inside Bending Radius:
6.000 inches
Bolt Hole Quantity:
4 1st end
Flange Outside Diameter:
1.750 inches 1st end
End Application:
3930-01-384-5310
Connection Style:
Plain w/ gasket groove (sae flanged head) 1st end
Bolt Hole Diameter:
0.406 inches 1st end
End Flange Construction:
Solid 1st end
End Connection Design:
Elbow 1st end
Connection Type:
Plain face flange 1st end
Burst Test Pressure:
1000.0 pounds per square inch
Layer Composition And Location:
1st layer braided textile yarn and 2nd layer helix wire coil and outer layer molded rubber, synthetic
Maximum Operating Pressure:
250.0 pounds per square inch
Hydrostatic Test Pressure:
500.0 pounds per square inch
Flow Angle:
90.0 degrees 1st end

Oil resistant and ozone resistant

**Outer Covering Environmental Protection:** 

**NSN 4720-01-416-6749**Nonmetallic Hose Assembly - Page 2 of 2



Inside Surface Condition:
Smooth
Measuring Method And Length:
955.0 millimeters working
Flange Style:
Round w/ bolt holes 1st end
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A542a0