

View Online at <https://aerobasegroup.com/nsn/4720-01-416-9635>

**Cross Sectional Shape:**

Round

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

2.000 inches

**Temperature Rating:**

-32.0 degrees celsius single response and 52.0 degrees celsius single response

**Outside Diameter:**

2.656 inches

**Minimum Inside Bending Radius:**

8.000 inches

**Hose Or Tubing Specification/std Data:**

Mil-h-370, type 2 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**End Application:**

5430-01-374-5656

**Connection Style:**

Plain 1st end

**End Connection Design:**

Straight 1st end

**End Fitting Component And Material:**

Complete fitting aluminum alloy all ends

**Fitting Component And Surface Treatment:**

Complete fitting anodize 1st end

**Connection Type:**

Threaded external pipe 1st end

**Second End Relationship With First End:**

Identical

**Burst Test Pressure:**

400.0 pounds per square inch

**First End Swivel Action Capability:**

Not included

**Layer Composition And Location:**

Outer layer molded rubber, chloroprene err-100

**Maximum Operating Pressure:**

100.0 pounds per square inch

**Thread Size:**

2.000 inches 1st end

**Hydrostatic Test Pressure:**

125.0 pounds per square inch

**Outer Covering Environmental Protection:**

Ozone resistant and oil resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

10.0 feet excluding end fittings

**Special Features:**

Suction and discharge hose

**Thread Series Designator:**

Npt 1st end

**Specification Data:**

81349-mil-h-370 government specification

**Specification Or Standard:**

B type and c class and 6 size

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0

**Mil-std (military Standard):**

Mil-h-370 spec.