NSN 4720-01-416-9662

Cold water hose

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-416-9662

| Cross Sectional Shape: | | |
|---|--|--|
| Round | | |
| Thread Class: | | |
| 3b 1st end | | |
| Thread Direction: | | |
| Right-hand 1st end | | |
| Inside Diameter: | | |
| 0.310 inches | | |
| Tempurature Rating: | | |
| -65.0 degrees fahrenheit single response and 300.0 degrees fahrenheit single response | | |
| Outside Diameter: | | |
| 0.500 inches | | |
| Minimum Inside Bending Radius: | | |
| 3.000 inches | | |
| End Application: | | |
| Aircraft, airlifter, c-17a | | |
| Connection Style: | | |
| Swivel nut, flareless 1st end | | |
| End Connection Design: | | |
| Straight 1st end | | |
| Connection Type: | | |
| Threaded internal tube 1st end | | |
| Burst Test Pressure: | | |
| 1200.0 pounds per square inch | | |
| Layer Composition And Location: | | |
| Outer layer braided polyamide cord | | |
| Maximum Operating Pressure: | | |
| 300.0 pounds per square inch | | |
| Thread Size: | | |
| 0.562 inches 2nd end | | |
| Seat Angle: | | |
| 37.0 degrees 2nd end | | |
| Hydrostatic Test Pressure: | | |
| 600.0 pounds per square inch | | |
| Flow Angle: | | |
| 90.0 degrees 2nd end | | |
| Inside Surface Condition: | | |
| Smooth | | |
| Measuring Method And Length: | | |
| 7.000 inches working | | |
| Special Features: | | |

NSN 4720-01-416-9662

Nonmetallic Hose Assembly - Page 2 of 2



| | | _ |
|--------|----------|-------------|
| Thread | l Series | Designator: |
| | | |

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0