Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-416-9663

ross Sectional Shape:
ound
hread Class:
b 1st end
hread Direction:
ight-hand 1st end
nside Diameter:
310 inches
empurature Rating:
5.0 degrees fahrenheit single response and 300.0 degrees fahrenheit single response
utside Diameter:
.500 inches
linimum Inside Bending Radius:
.000 inches
ngle Between Rigid Elbow Fittings In Deg:
0.0
nd Application:
ircraft, airlifter, c-17a
onnection Style:
wivel nut, flareless 2nd end
nd Connection Design:
lbow 2nd end
onnection Type:
hreaded internal tube 1st end
urst Test Pressure:
200.0 pounds per square inch
ayer Composition And Location:
uter layer braided polyamide cord
laximum Operating Pressure:
00.0 pounds per square inch
hread Size:
.562 inches 2nd end
eat Angle:
2.0 degrees 2nd end
ydrostatic Test Pressure:
00.0 pounds per square inch
low Angle:
0.0 degrees 2nd end
side Surface Condition:
mooth
leasuring Method And Length:
.000 inches working

Special Features:

Hot water hose assembly

Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

