## NSN 4720-01-417-4920

**Cross Sectional Shape:** 

Round

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-417-4920

Thread Class:			
3b 1st end			
Thread Direction:			
Right-hand 1st end			
Inside Diameter:			
0.380 inches			
Tempurature Rating:			
-40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response			
Outside Diameter:			
0.750 inches			
Minimum Inside Bending Radius:			
5.000 inches			
End Application:			
2350-01-390-4683			
Connection Style:			
Swivel nut, gasket seal 1st end			
End Connection Design:			
Straight 1st end			
Connection Type:			
Threaded internal tube 1st end			
Thready Qty Per Inch (tpi):			
16 1st end			
Burst Test Pressure:			
20000.0 pounds per square inch			
Layer Composition And Location:			
1st layer braided wire and 2nd layer braided wire and outer layer molded rubber, synthetic			
Maximum Operating Pressure:			
5000.0 pounds per square inch			
Thread Size:			
0.438 inches 1st end			
Hydrostatic Test Pressure:			
10000.0 pounds per square inch			
Outer Covering Environmental Protection:			
Oil resistant and weatherproof			
Inside Surface Condition:			
Smooth			
Measuring Method And Length:			
78.000 inches			
Media For Which Designed:			
Fuel/oil, hydrocarbon and hydraulic fluid, water base single response			

## NSN 4720-01-417-4920

Nonmetallic Hose Assembly - Page 2 of 2



Inrea	d Series	Designator:
Un 1st	end	

Shelf Life:

Unit Of Measure:

N/a

Demilitarization:

No

Fiig:

A542a0