

View Online at <https://aerobasegroup.com/nsn/4720-01-417-5861>

**Cross Sectional Shape:**

Round

**Thread Class:**

2b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.750 inches

**Temperature Rating:**

-40.0 degrees fahrenheit single response and 250.0 degrees fahrenheit single response

**Outside Diameter:**

1.260 inches

**Minimum Inside Bending Radius:**

11.000 inches

**Hose Or Tubing Specification/std Data:**

Sae j517, 100r11-81343 standard (includes industry or association standards, individual manufactureer standards, etc.).

**End Application:**

2350-01-390-4683

**Connection Style:**

Swivel nut, gasket seal 2nd end

**End Connection Design:**

Straight 1st end

**End Fitting Component And Material:**

Complete fitting steel all ends

**Connection Type:**

Threaded internal tube 1st end

**Thready Qty Per Inch (tpi):**

12 2nd end

**Second End Relationship With First End:**

Not identical

**First End Swivel Action Capability:**

Not included

**Layer Composition And Location:**

1st layer spirally laid steel wire err-100

**Maximum Operating Pressure:**

5000.0 pounds per square inch

**Thread Size:**

1.188 inches 2nd end

**Hydrostatic Test Pressure:**

10000.0 pounds per square inch

**Flow Angle:**

90.0 degrees 2nd end

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

40.000 inches

**Second End Swivel Action Capability:**

Not included

**Special Features:**

Inner conveying tube material-rubber, synthetic

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Thread Series Designator:**

Un 2nd end

**Specification Data:**

Sae j517, 100r11-81343 national std/spec

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A542a0