Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-417-5868

Cross Sectional Shape:	
Round	
Thread Class:	
2b 1st end	
Thread Direction:	
Right-hand 1st end	
nside Diameter:	
0.380 inches	
Fempurature Rating:	
40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response	
Dutside Diameter:	
0.750 inches	
Ainimum Inside Bending Radius:	
5.000 inches	
End Application:	
2350-01-390-4683	
Connection Style:	
Swivel nut flare 1st end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded internal tube 1st end	
Burst Test Pressure:	
000.0 pounds per square inch	
ayer Composition And Location:	
st layer braided wire and 2nd layer braided wire and outer layer molded ru	bber, synthetic
Maximum Operating Pressure:	
500.0 pounds per square inch	
Thread Size:	
0.188 inches 1st end	
Seat Angle:	
37.0 degrees 1st end	
Hydrostatic Test Pressure:	
3000.0 pounds per square inch	
nside Surface Condition:	
Smooth	
Measuring Method And Length:	
67.000 inches	
Media For Which Designed:	
Fuel/oil, hydrocarbon and hydraulic fluid, water base single response	
Thread Series Designator:	
Jnjf 1st end	

NSN 4720-01-417-5868

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0

