

View Online at <https://aerobasegroup.com/nsn/4720-01-417-6681>

Cross Sectional Shape:

Round

Inside Diameter:

1.500 inches

Temperature Rating:

-40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response

Flange Thickness:

0.315 inches 2nd end

Outside Diameter:

2.080 inches

Minimum Inside Bending Radius:

10.000 inches

Center To Center Distance Between Bolt Holes Along Width:

1.406 inches 2nd end

Center To Center Distance Between Bolt Holes Along Length:

2.750 inches 2nd end

Bolt Hole Quantity:

4 2nd end

Flange Length:

3.660 inches and 3.720 inches 2nd end

End Application:

2350-01-390-4683

Flange Width:

3.160 inches 2nd end

Connection Style:

Plain 2nd end

Bolt Hole Diameter:

0.531 inches 2nd end

End Flange Construction:

Solid 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Plain face flange 2nd end

Burst Test Pressure:

600.0 pounds per square inch

Layer Composition And Location:

1st layer braided textile yarn and 2nd layer helix wire coil and 3rd layer braided textile yarn and outer layer molded rubber, synthetic

Maximum Operating Pressure:

150.0 pounds per square inch

Hydrostatic Test Pressure:

300.0 pounds per square inch

Flow Angle:

45.0 degrees 2nd end

Inside Surface Condition:

Smooth

Measuring Method And Length:

21.000 inches

Flange Style:

Double oval (sae split type flange) 1st end

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0