

View Online at <https://aerobasegroup.com/nsn/4720-01-417-9462>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

1.000 inches

**Temperature Rating:**

-65.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response

**Outside Diameter:**

1.312 inches

**Minimum Inside Bending Radius:**

3.000 inches

**End Application:**

Aircraft, airlifter c-17a

**Connection Style:**

Swivel nut, flareless 2nd end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded internal tube 1st end

**Features Provided:**

Internal support

**Thready Qty Per Inch (tpi):**

12 2nd end

**Burst Test Pressure:**

800.0 pounds per square inch

**Layer Composition And Location:**

Outer layer braided polyamide cord

**Maximum Operating Pressure:**

200.0 pounds per square inch

**Thread Size:**

1.625 inches 2nd end

**Seat Angle:**

12.0 degrees 2nd end

**Hydrostatic Test Pressure:**

400.0 pounds per square inch

**Flow Angle:**

45.0 degrees 2nd end

**Inside Surface Condition:**

Convuluted

**Measuring Method And Length:**

29.250 inches working

**Thread Series Designator:**

Unj 2nd end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0