

View Online at <https://aerobasegroup.com/nsn/4720-01-417-9491>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

1.250 inches

Temperature Rating:

-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

Flange Thickness:

0.315 inches 2nd end

Outside Diameter:

1.960 inches

Minimum Inside Bending Radius:

16.500 inches

Exterior Color:

Brown

Center To Center Distance Between Bolt Holes Along Width:

1.035 inches 2nd end

Center To Center Distance Between Bolt Holes Along Length:

2.062 inches 2nd end

Bolt Hole Quantity:

4 2nd end

Flange Length:

2.720 inches and 2.780 inches 2nd end

End Application:

2350-01-390-4683

Flange Width:

2.900 inches 2nd end

Connection Style:

Swivel nut, gasket seal 1st end

Bolt Hole Diameter:

0.406 inches 2nd end

End Flange Construction:

Solid 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

12 1st end

Burst Test Pressure:

20000.0 pounds per square inch

Layer Composition And Location:

1st layer spirally laid steel wire and 2nd layer spirally laid steel wire and 3rd layer spirally laid steel wire and 4th layer spirally laid steel wire and 5th layer spirally laid steel wire and 6th layer spirally laid steel wire and outer layer molded rubber, synthetic

Maximum Operating Pressure:

5000.0 pounds per square inch

Thread Size:

1.688 inches 1st end

Hydrostatic Test Pressure:

10000.0 pounds per square inch

Flow Angle:

45.0 degrees 2nd end

Outer Covering Environmental Protection:

Weatherproof and oil resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

59.500 inches working

Flange Style:

Double oval (sae split type flange) 2nd end

Media For Which Designed:

Fuel/oil, hydrocarbon and hydraulic fluid, water base single response

Thread Series Designator:

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0