

View Online at <https://aerobasegroup.com/nsn/4720-01-417-9508>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.625 inches

Temperature Rating:

-40.0 degrees celsius and 135.0 degrees celsius single response

Outside Diameter:

Between 0.875 inches and 0.938 inches

Minimum Inside Bending Radius:

127.0 millimeters

End Application:

Strategic sealift conversion ships class

Connection Style:

Swivel nut, gasket seal 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

14 2nd end

Burst Test Pressure:

1400.0 pounds per square inch

Layer Composition And Location:

1st layer braided textile yarn and outer layer molded rubber, synthetic

Maximum Operating Pressure:

2413.0 kilopascals

Thread Size:

1.000 inches 2nd end

Hydrostatic Test Pressure:

700.0 pounds per square inch

Flow Angle:

45.0 degrees 2nd end

Outer Covering Environmental Protection:

Oil resistant and weatherproof

Inside Surface Condition:

Smooth

Measuring Method And Length:

1626.0 millimeters working

Special Features:

Lower left hose assembly

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Uns 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A542a0