NSN 4720-01-418-0284

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-418-0284

| Cross Sectional Shape: |
|--|
| Round |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.188 inches |
| Tempurature Rating: |
| -65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.500 inches |
| Minimum Inside Bending Radius: |
| 4.000 inches |
| End Application: |
| 2350-01-390-4683 |
| Connection Style: |
| Plain 1st end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded external pipe 1st end |
| Burst Test Pressure: |
| 12000.0 pounds per square inch |
| Layer Composition And Location: |
| 1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, chloroprene |
| Maximum Operating Pressure: |
| 3000.0 pounds per square inch |
| Thread Size: |
| 0.125 inches 1st end |
| Hydrostatic Test Pressure: |
| 6000.0 pounds per square inch |
| Outer Covering Environmental Protection: |
| Oil resistant and ozone resistant and mildew resistant |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 38.000 inches |
| Media For Which Designed: |
| Fuel/oil, hydrocarbon single response |
| Thread Series Designator: |
| Nptf 1st end |
| Shelf Life: |
| N/a |

NSN 4720-01-418-0284

Nonmetallic Hose Assembly - Page 2 of 2



| | 1 | :. | ~ | 84 | | | | |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

No

Fiig:

A542a0