## NSN 4720-01-418-0293

Unf 2nd end

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-418-0293

Cross Sectional Shape:					
Round					
Thread Class:					
2b 1st end					
Thread Direction:					
Right-hand 1st end					
Inside Diameter:					
0.367 inches					
Tempurature Rating:					
-55.0 degrees fahrenheit and 250.0 degrees fahrenheit single response					
Outside Diameter:					
0.674 inches					
Minimum Inside Bending Radius:					
5.000 inches					
End Application:					
2350-01-248-7620: fighting vehicle systems, bradle (bfvs)					
Connection Style:					
Swivel nut flare 2nd end					
End Connection Design:					
Straight 1st end					
Connection Type:					
Threaded internal tube 1st end					
Burst Test Pressure:					
16000.0 pounds per square inch					
Layer Composition And Location:					
1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, chloroprene					
Maximum Operating Pressure:					
4000.0 pounds per square inch					
Thread Size:					
0.750 inches 1st end					
Seat Angle:					
37.0 degrees 2nd end					
Hydrostatic Test Pressure:					
8000.0 pounds per square inch					
Flow Angle:					
90.0 degrees 2nd end					
Inside Surface Condition:					
Smooth					
Measuring Method And Length:					
24.000 inches					
Thread Sories Designator:					

## NSN 4720-01-418-0293

Nonmetallic Hose Assembly - Page 2 of 2



_				
c	hο	.1+		ife:
J	116		_	HG.

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0