Nonmetallic Hose Assembly - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/4720-01-418-2130



Cross Sectional Shape:

Round

Inside Diameter:

1.000 inches

Tempurature Rating:

-40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response

Flange Thickness:

0.315 inches 2nd end

Outside Diameter:

1.500 inches

Minimum Inside Bending Radius:

12.000 inches

Center To Center Distance Between Bolt Holes Along Width:

1.188 inches 2nd end

Center To Center Distance Between Bolt Holes Along Length:

2.312 inches 2nd end

Bolt Hole Quantity:

4 2nd end

Flange Length:

3.090 inches and 3.160 inches 2nd end

End Application:

2350-01-390-4683

Flange Width:

2.780 inches 2nd end

Connection Style:

Plain w/ gasket groove (sae flanged head) 2nd end

Bolt Hole Diameter:

0.469 inches 2nd end

End Flange Construction:

Solid 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Plain face flange 2nd end

Layer Composition And Location:

1st layer braided wire and 2nd layer braided wire and outer layer wrapped rubber, synthetic

Maximum Operating Pressure:

1500.0 pounds per square inch

Hydrostatic Test Pressure:

3000.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Nonmetallic Hose Assembly - Page 2 of 2



Inside Surface Condition: Smooth Measuring Method And Length: 33.000 inches Flange Style: Double oval (sae split type flange) 1st end Media For Which Designed: Fuel/oil, hydrocarbon single response Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A542a0