

View Online at <https://aerobasegroup.com/nsn/4720-01-418-3516>

Cross Sectional Shape:

Round

Inside Diameter:

1.000 inches

Temperature Rating:

-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

Flange Thickness:

0.405 inches 2nd end

Outside Diameter:

1.520 inches

Minimum Inside Bending Radius:

12.000 inches

Angle Between Rigid Elbow Fittings In Deg:

160.0

Center To Center Distance Between Bolt Holes Along Width:

1.350 inches 2nd end

Center To Center Distance Between Bolt Holes Along Length:

2.250 inches 1st end

Bolt Hole Quantity:

4 2nd end

Flange Length:

3.720 inches and 3.780 inches 2nd end

End Application:

2350-01-390-4683

Flange Width:

2.660 inches 1st end

Connection Style:

Plain w/ gasket groove (sae flanged head) 2nd end

Bolt Hole Diameter:

0.469 inches 1st end

End Flange Construction:

Solid 2nd end

End Connection Design:

Elbow 2nd end

Connection Type:

Plain face flange 2nd end

Burst Test Pressure:

20000.0 pounds per square inch

Layer Composition And Location:

1st layer spirally laid steel wire and 2nd layer spirally laid steel wire and 3rd layer spirally laid steel wire and 4th layer spirally laid steel wire and outer layer wrapped rubber, synthetic

Maximum Operating Pressure:

5000.0 pounds per square inch

Hydrostatic Test Pressure:

10000.0 pounds per square inch

Flow Angle:

45.0 degrees 2nd end

Inside Surface Condition:

Smooth

Measuring Method And Length:

21.750 inches

Flange Style:

Double oval (sae split type flange) 1st end

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0