NSN 4720-01-418-3526

Cross Sectional Shape:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-418-3526

Round	
Inside Diameter:	
1.250 inches	
Tempurature Rating:	
-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response	
Flange Thickness:	
0.405 inches 1st end	
Outside Diameter:	
1.960 inches	
Minimum Inside Bending Radius:	
16.500 inches	
Exterior Color:	
Brown	
Angle Between Rigid Elbow Fittings In Deg:	
180.0	
Center To Center Distance Between Bolt Holes Along Width:	
1.250 inches 1st end	
Center To Center Distance Between Bolt Holes Along Length:	
2.625 inches 1st end	
Bolt Hole Quantity:	
4 1st end	
Flange Length:	
3.720 inches and 3.780 inches 1st end	
End Application:	
2350-01-390-4683	
Flange Width:	
2.960 inches 1st end	
Connection Style:	
Plain w/ gasket groove (sae flanged head) 1st end	
Bolt Hole Diameter:	
0.531 inches 1st end	
End Flange Construction:	
Solid 1st end	
End Connection Design:	
Elbow 1st end	
Connection Type:	
Plain face flange 1st end	
Burst Test Pressure:	
20000.0 pounds per square inch	
Layer Composition And Location	

1st layer spirally laid steel wire and 2nd layer spirally laid steel wire and 3rd layer spirally laid steel wire and 4th layer spirally laid steel wire

and 5th layer spirally laid steel wire and 6th layer spirally laid steel wire and outer layer molded rubber, synthetic

NSN 4720-01-418-3526

Nonmetallic Hose Assembly - Page 2 of 2



Maximum Operating Pressure:
5000.0 pounds per square inch
Hydrostatic Test Pressure:
10000.0 pounds per square inch
Flow Angle:
90.0 degrees 1st end
Inside Surface Condition:
Smooth
Measuring Method And Length:
14.940 inches
Flange Style:
Double oval (sae split type flange) 1st end
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A542a0