

View Online at <https://aerobasegroup.com/nsn/4720-01-418-3526>

Cross Sectional Shape:

Round

Inside Diameter:

1.250 inches

Temperature Rating:

-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

Flange Thickness:

0.405 inches 1st end

Outside Diameter:

1.960 inches

Minimum Inside Bending Radius:

16.500 inches

Exterior Color:

Brown

Angle Between Rigid Elbow Fittings In Deg:

180.0

Center To Center Distance Between Bolt Holes Along Width:

1.250 inches 1st end

Center To Center Distance Between Bolt Holes Along Length:

2.625 inches 1st end

Bolt Hole Quantity:

4 1st end

Flange Length:

3.720 inches and 3.780 inches 1st end

End Application:

2350-01-390-4683

Flange Width:

2.960 inches 1st end

Connection Style:

Plain w/ gasket groove (sae flanged head) 1st end

Bolt Hole Diameter:

0.531 inches 1st end

End Flange Construction:

Solid 1st end

End Connection Design:

Elbow 1st end

Connection Type:

Plain face flange 1st end

Burst Test Pressure:

20000.0 pounds per square inch

Layer Composition And Location:

1st layer spirally laid steel wire and 2nd layer spirally laid steel wire and 3rd layer spirally laid steel wire and 4th layer spirally laid steel wire and 5th layer spirally laid steel wire and 6th layer spirally laid steel wire and outer layer molded rubber, synthetic

Maximum Operating Pressure:

5000.0 pounds per square inch

Hydrostatic Test Pressure:

10000.0 pounds per square inch

Flow Angle:

90.0 degrees 1st end

Inside Surface Condition:

Smooth

Measuring Method And Length:

14.940 inches

Flange Style:

Double oval (sae split type flange) 1st end

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0