NSN 4720-01-418-4244

Fuel/oil, hydrocarbon single response

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-418-4244

Cross Sectional Shape:
Round
Thread Class:
3a 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.310 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response
Outside Diameter:
0.610 inches
Minimum Inside Bending Radius:
2.000 inches
Connection Style:
Inverted flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded external tube 1st end
Thready Qty Per Inch (tpi):
18 1st end
Burst Test Pressure:
1000.0 pounds per square inch
Layer Composition And Location:
1st layer braided corrosion resistant steel wire, partial coverage and outer layer rubber impregnated braided fabric
Maximum Operating Pressure:
250.0 pounds per square inch
Thread Size:
0.562 inches 1st end
Seat Angle:
45.0 degrees 1st end
Hydrostatic Test Pressure:
500.0 pounds per square inch
Vacuum In Torr:
50.8
Inside Surface Condition:
Smooth
Measuring Method And Length:
29.250 inches working
Media For Which Designed:

NSN 4720-01-418-4244

Nonmetallic Hose Assembly - Page 2 of 2



T	ſh	r	ea	d	Seri	es	Desi	igna	tor:	

Unj 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0