NSN 4720-01-418-4265

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-418-4265

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
1.000 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
1.500 inches
Minimum Inside Bending Radius:
8.000 inches
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
12 2nd end
Burst Test Pressure:
2250.0 pounds per square inch
Layer Composition And Location:
1st layer braided fiber and 2nd layer braided fiber and outer layer molded rubber, chloroprene
Maximum Operating Pressure:
560.0 pounds per square inch
Thread Size:
1.312 inches 2nd end
Seat Angle:
37.0 degrees 2nd end
Flow Angle:
90.0 degrees 2nd end
Inside Surface Condition:
Smooth
Measuring Method And Length:
16.750 inches
Thread Series Designator:
Un 2nd end
Shelf Life:

N/a

NSN 4720-01-418-4265

Nonmetallic Hose Assembly - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A542a0