NSN 4720-01-418-6505

Nonmetallic Hose - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-01-418-6505

| Cross Sectional Shape: |
|---|
| Round |
| Inside Diameter: |
| 0.500 inches |
| Tempurature Rating: |
| -40.0 degrees fahrenheit single response and 212.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.810 inches |
| Minimum Inside Bending Radius: |
| 3.500 inches |
| Exterior Color: |
| Black |
| End Application: |
| 3895-01-344-5480 |
| Burst Test Pressure: |
| 14000.0 pounds per square inch single response |
| Layer Composition And Location: |
| 1st layer braided wire err-100 |
| Maximum Operating Pressure: |
| 3500.0 pounds per square inch single response |
| Hydrostatic Test Pressure: |
| 7000.0 pounds per square inch single response |
| Outer Covering Environmental Protection: |
| Abrasion resistant and oil resistant and weatherproof |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 100.0 feet |
| Material: |
| Rubber synthetic tube |
| Media For Which Designed: |
| Fuel/oil, hydrocarbon single response |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A541z0 |