## NSN 4720-01-419-0553



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-01-419-0553 **Cross Sectional Shape:** Round **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.188 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 100.0 degrees fahrenheit single response **Outside Diameter:** 0.470 inches **Minimum Inside Bending Radius:** 3.500 inches **End Application:** 3895-01-344-5480 **Connection Style:** Plain 2nd end **End Connection Design:** Straight 2nd end **Connection Type:** Threaded external pipe 2nd end **Burst Test Pressure:** 12000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided steel wire and outer layer molded rubber, synthetic **Maximum Operating Pressure:** 3000.0 pounds per square inch **Thread Size:** 0.250 inches 2nd end **Hydrostatic Test Pressure:** 6000.0 pounds per square inch **Outer Covering Environmental Protection:** Abrasion resistant and oil resistant **Inside Surface Condition:** Smooth **Measuring Method And Length:** 27.000 inches Media For Which Designed: Fuel/oil, hydrocarbon single response **Thread Series Designator:** 

Nptf 2nd end

Shelf Life:

N/a

## NSN 4720-01-419-0553

Nonmetallic Hose Assembly - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A542a0