

View Online at <https://aerobasegroup.com/nsn/4720-01-419-1657>

Cross Sectional Shape:

Round

Inside Diameter:

1.250 inches

Temperature Rating:

-40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response

Flange Thickness:

0.315 inches 2nd end

Outside Diameter:

1.920 inches

Minimum Inside Bending Radius:

16.500 inches

Center To Center Distance Between Bolt Holes Along Width:

1.188 inches 2nd end

Center To Center Distance Between Bolt Holes Along Length:

2.312 inches 2nd end

Bolt Hole Quantity:

4 2nd end

Flange Length:

3.090 inches and 3.160 inches 2nd end

End Application:

2350-01-390-4683

Flange Width:

2.780 inches 2nd end

Connection Style:

Plain w/ gasket groove (sae flanged head) 2nd end

Bolt Hole Diameter:

0.469 inches 2nd end

End Flange Construction:

Solid 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Plain face flange 2nd end

Burst Test Pressure:

1200.0 pounds per square inch

Layer Composition And Location:

1st layer braided wire and 2nd layer braided wire and outer layer wrapped rubber, synthetic

Maximum Operating Pressure:

300.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Vacuum In Torr:

50.8

Inside Surface Condition:

Smooth

Measuring Method And Length:

25.750 inches

Flange Style:

Double oval (sae split type flange) 1st end

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0