

View Online at <https://aerobasegroup.com/nsn/4720-01-419-2604>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.500 inches

Outside Diameter:

0.920 inches

Minimum Inside Bending Radius:

7.000 inches

Inner Conveying Tube Style:

Annular close-pitch corrugated

End Application:

2350-01-390-4683

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Identical ends

Thready Qty Per Inch (tpi):

12 1st end

Burst Test Pressure:

3500.0 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Unable To Decode:

Unable to decode or unable to decode or unable to decode

Maximum Operating Pressure:

875.0 pounds per square inch

Unable To Decode:

Unable to decode or unable to decode

Thread Size:

1.062 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

1750.0 pounds per square inch

Measuring Method And Length:

34.880 inches working

Thread Series Designator:

Uns 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0