

View Online at <https://aerobasegroup.com/nsn/4720-01-419-4751>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

1.000 inches

**Temperature Rating:**

-40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response

**Outside Diameter:**

1.500 inches

**Minimum Inside Bending Radius:**

12.000 inches

**End Application:**

2350-01-390-4683

**Connection Style:**

Swivel nut flare 2nd end

**End Connection Design:**

Straight 2nd end

**Connection Type:**

Threaded internal tube 1st end

**Thread Qty Per Inch (tpi):**

12 2nd end

**Burst Test Pressure:**

6000.0 pounds per square inch

**Layer Composition And Location:**

1st layer braided wire and 2nd layer braided wire and outer layer wrapped rubber, synthetic

**Maximum Operating Pressure:**

1500.0 pounds per square inch

**Thread Size:**

1.062 inches 1st end

**Seat Angle:**

37.0 degrees 2nd end

**Hydrostatic Test Pressure:**

3000.0 pounds per square inch

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

56.000 inches

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Thread Series Designator:**

Un 2nd end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A542a0