NSN 4720-01-419-4753

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-419-4753

Cross Sectional Shape:				
Round				
Thread Class:				
3b 1st end				
Thread Direction:				
Right-hand 1st end				
Inside Diameter:				
1.000 inches				
Tempurature Rating:				
-40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response				
Outside Diameter:				
1.500 inches				
Minimum Inside Bending Radius:				
12.000 inches				
End Application:				
2350-01-390-4683				
Connection Style:				
Swivel nut flare 2nd end				
End Connection Design:				
Straight 2nd end				
Connection Type:				
Threaded internal tube 1st end				
Thready Qty Per Inch (tpi):				
12 2nd end				
Burst Test Pressure:				
6000.0 pounds per square inch				
Layer Composition And Location:				
1st layer braided wire and 2nd layer braided wire and outer layer wrapped rubber, synthetic				
Maximum Operating Pressure:				
1500.0 pounds per square inch				
Thread Size:				
1.062 inches 1st end				
Seat Angle:				
37.0 degrees 2nd end				
Hydrostatic Test Pressure:				
3000.0 pounds per square inch				
Inside Surface Condition:				
Smooth				
Measuring Method And Length:				
18.000 inches				
Media For Which Designed:				

Fuel/oil, hydrocarbon single response

NSN 4720-01-419-4753

Nonmetallic Hose Assembly - Page 2 of 2



Th	road	Series	Docin	nator:
ιn	reau	Series	Desig	mator:

Un 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0