## NSN 4720-01-419-4767

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-419-4767 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.625 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response **Outside Diameter:** 1.000 inches **Minimum Inside Bending Radius:** 8.000 inches **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 14500.0 pounds per square inch **Layer Composition And Location:** 1st layer braided steel wire and 2nd layer molded rubber, synthetic and 3rd layer braided steel wire and outer layer molded rubber, synthetic **Maximum Operating Pressure:** 3600.0 pounds per square inch **Thread Size:** 0.875 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 7200.0 pounds per square inch **Inside Surface Condition:** Smooth **Measuring Method And Length:** 43.000 inches

Media For Which Designed: Fuel/oil, hydrocarbon single response **Thread Series Designator:** 

Unif 1st end

Shelf Life:

N/a

## NSN 4720-01-419-4767

Nonmetallic Hose Assembly - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A542a0