## NSN 4720-01-419-6481

Nonmetallic Hose - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-01-419-6481

Cross Sectional Shape:  Round  Inside Diameter: 0.500 inches  Tempurature Rating: -40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response  Outside Diameter: 0.750 inches  Minimum Inside Bending Radius: 3.000 inches  End Application: Seawolf class ssn  Burst Test Pressure: 1000.0 pounds per square inch single response  Layer Composition And Location: 1st layer braided textile yarn err-100  Maximum Operating Pressure: 250.0 pounds per square inch single response  Hydrostatic Test Pressure: 500.0 pounds per square inch single response  Outer Covering Environmental Protection: Oil resistant and weatherproof  Inside Surface Condition: Smooth  Measuring Method And Length: 25.0 feet  Material: Rubber synthetic tube
Inside Diameter:  0.500 inches  Tempurature Rating: -40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response  Outside Diameter: 0.750 inches  Minimum Inside Bending Radius: 3.000 inches  End Application: Seawolf class ssn  Burst Test Pressure: 1000.0 pounds per square inch single response  Layer Composition And Location: 1st layer braided textile yarn err-100  Maximum Operating Pressure: 250.0 pounds per square inch single response  Hydrostatic Test Pressure: 500.0 pounds per square inch single response  Outer Covering Environmental Protection: Oil resistant and weatherproof  Inside Surface Condition: Smooth  Measuring Method And Length: 25.0 feet  Material:
O.500 inches Tempurature Rating: -40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response Outside Diameter: 0.750 inches Minimum Inside Bending Radius: 3.000 inches End Application: Seawolf class ssn Burst Test Pressure: 1000.0 pounds per square inch single response Layer Composition And Location: 1st layer braided textile yarn err-100 Maximum Operating Pressure: 250.0 pounds per square inch single response Hydrostatic Test Pressure: 500.0 pounds per square inch single response Outer Covering Environmental Protection: Oil resistant and weatherproof Inside Surface Condition: Smooth Measuring Method And Length: 25.0 feet Material:
Tempurature Rating: -40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response  Outside Diameter: 0.750 inches  Minimum Inside Bending Radius: 3.000 inches  End Application: Seawolf class ssn  Burst Test Pressure: 1000.0 pounds per square inch single response  Layer Composition And Location: 1st layer braided textile yarn err-100  Maximum Operating Pressure: 250.0 pounds per square inch single response  Hydrostatic Test Pressure: 500.0 pounds per square inch single response  Outer Covering Environmental Protection: Oil resistant and weatherproof Inside Surface Condition: Smooth  Measuring Method And Length: 25.0 feet  Material:
-40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response  Outside Diameter: 0.750 inches  Minimum Inside Bending Radius: 3.000 inches  End Application: Seawolf class ssn  Burst Test Pressure: 1000.0 pounds per square inch single response Layer Composition And Location: 1st layer braided textile yarn err-100  Maximum Operating Pressure: 250.0 pounds per square inch single response Hydrostatic Test Pressure: 500.0 pounds per square inch single response Outer Covering Environmental Protection: Oil resistant and weatherproof Inside Surface Condition: Smooth  Measuring Method And Length: 25.0 feet Material:
Outside Diameter:  0.750 inches  Minimum Inside Bending Radius: 3.000 inches  End Application: Seawolf class ssn  Burst Test Pressure: 1000.0 pounds per square inch single response Layer Composition And Location: 1st layer braided textile yarn err-100  Maximum Operating Pressure: 250.0 pounds per square inch single response Hydrostatic Test Pressure: 500.0 pounds per square inch single response Outer Covering Environmental Protection: Oil resistant and weatherproof Inside Surface Condition: Smooth Measuring Method And Length: 25.0 feet Material:
Minimum Inside Bending Radius: 3.000 inches End Application: Seawolf class ssn Burst Test Pressure: 1000.0 pounds per square inch single response Layer Composition And Location: 1st layer braided textile yarn err-100 Maximum Operating Pressure: 250.0 pounds per square inch single response Hydrostatic Test Pressure: 500.0 pounds per square inch single response Outer Covering Environmental Protection: Oil resistant and weatherproof Inside Surface Condition: Smooth Measuring Method And Length: 25.0 feet Material:
Minimum Inside Bending Radius: 3.000 inches End Application: Seawolf class ssn Burst Test Pressure: 1000.0 pounds per square inch single response Layer Composition And Location: 1st layer braided textile yarn err-100 Maximum Operating Pressure: 250.0 pounds per square inch single response Hydrostatic Test Pressure: 500.0 pounds per square inch single response Outer Covering Environmental Protection: Oil resistant and weatherproof Inside Surface Condition: Smooth Measuring Method And Length: 25.0 feet Material:
3.000 inches  End Application: Seawolf class ssn  Burst Test Pressure: 1000.0 pounds per square inch single response Layer Composition And Location: 1st layer braided textile yarn err-100  Maximum Operating Pressure: 250.0 pounds per square inch single response Hydrostatic Test Pressure: 500.0 pounds per square inch single response Outer Covering Environmental Protection: Oil resistant and weatherproof Inside Surface Condition: Smooth Measuring Method And Length: 25.0 feet Material:
End Application: Seawolf class ssn Burst Test Pressure: 1000.0 pounds per square inch single response Layer Composition And Location: 1st layer braided textile yarn err-100 Maximum Operating Pressure: 250.0 pounds per square inch single response Hydrostatic Test Pressure: 500.0 pounds per square inch single response Outer Covering Environmental Protection: Oil resistant and weatherproof Inside Surface Condition: Smooth Measuring Method And Length: 25.0 feet Material:
Seawolf class ssn  Burst Test Pressure:  1000.0 pounds per square inch single response  Layer Composition And Location:  1st layer braided textile yarn err-100  Maximum Operating Pressure:  250.0 pounds per square inch single response  Hydrostatic Test Pressure:  500.0 pounds per square inch single response  Outer Covering Environmental Protection:  Oil resistant and weatherproof  Inside Surface Condition:  Smooth  Measuring Method And Length:  25.0 feet  Material:
Burst Test Pressure:  1000.0 pounds per square inch single response  Layer Composition And Location:  1st layer braided textile yarn err-100  Maximum Operating Pressure:  250.0 pounds per square inch single response  Hydrostatic Test Pressure:  500.0 pounds per square inch single response  Outer Covering Environmental Protection:  Oil resistant and weatherproof  Inside Surface Condition:  Smooth  Measuring Method And Length:  25.0 feet  Material:
1000.0 pounds per square inch single response  Layer Composition And Location:  1st layer braided textile yarn err-100  Maximum Operating Pressure:  250.0 pounds per square inch single response  Hydrostatic Test Pressure:  500.0 pounds per square inch single response  Outer Covering Environmental Protection:  Oil resistant and weatherproof  Inside Surface Condition:  Smooth  Measuring Method And Length:  25.0 feet  Material:
Layer Composition And Location:  1st layer braided textile yarn err-100  Maximum Operating Pressure:  250.0 pounds per square inch single response  Hydrostatic Test Pressure:  500.0 pounds per square inch single response  Outer Covering Environmental Protection:  Oil resistant and weatherproof  Inside Surface Condition:  Smooth  Measuring Method And Length:  25.0 feet  Material:
1st layer braided textile yarn err-100  Maximum Operating Pressure: 250.0 pounds per square inch single response  Hydrostatic Test Pressure: 500.0 pounds per square inch single response  Outer Covering Environmental Protection: Oil resistant and weatherproof Inside Surface Condition: Smooth  Measuring Method And Length: 25.0 feet  Material:
Maximum Operating Pressure:  250.0 pounds per square inch single response  Hydrostatic Test Pressure:  500.0 pounds per square inch single response  Outer Covering Environmental Protection:  Oil resistant and weatherproof  Inside Surface Condition:  Smooth  Measuring Method And Length:  25.0 feet  Material:
250.0 pounds per square inch single response  Hydrostatic Test Pressure: 500.0 pounds per square inch single response  Outer Covering Environmental Protection: Oil resistant and weatherproof Inside Surface Condition: Smooth  Measuring Method And Length: 25.0 feet  Material:
Hydrostatic Test Pressure:  500.0 pounds per square inch single response  Outer Covering Environmental Protection:  Oil resistant and weatherproof  Inside Surface Condition:  Smooth  Measuring Method And Length:  25.0 feet  Material:
500.0 pounds per square inch single response  Outer Covering Environmental Protection: Oil resistant and weatherproof Inside Surface Condition: Smooth  Measuring Method And Length: 25.0 feet  Material:
Outer Covering Environmental Protection: Oil resistant and weatherproof Inside Surface Condition: Smooth Measuring Method And Length: 25.0 feet Material:
Oil resistant and weatherproof Inside Surface Condition: Smooth Measuring Method And Length: 25.0 feet Material:
Inside Surface Condition: Smooth  Measuring Method And Length: 25.0 feet  Material:
Smooth  Measuring Method And Length: 25.0 feet  Material:
Measuring Method And Length: 25.0 feet Material:
25.0 feet  Material:
Material:
Ruhher synthetic tuhe
Rubber Synthetic tube
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A541z0