

View Online at <https://aerobasegroup.com/nsn/4720-01-420-0641>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.313 inches

Outside Diameter:

0.446 inches

Minimum Inside Bending Radius:

4.000 inches

Angle Between Rigid Elbow Fittings In Deg:

270.0

Connection Style:

Inverted flare 2nd end

End Connection Design:

Elbow 2nd end

Connection Type:

Threaded external tube 2nd end

Thready Qty Per Inch (tpi):

18 1st end

Burst Test Pressure:

9000.0 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

1500.0 pounds per square inch

Thread Size:

0.5625 inches 1st end

Seat Angle:

37.0 degrees 2nd end

Hydrostatic Test Pressure:

3000.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Vacuum In Torr:

28.0

Inside Surface Condition:

Smooth

Measuring Method And Length:

22.250 inches working and 22.750 inches working

Special Features:

Fireproof sleeve

Thread Series Designator:

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0