

View Online at <https://aerobasegroup.com/nsn/4720-01-420-2123>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.438 inches

**Temperature Rating:**

-65.0 degrees fahrenheit and 450.0 degrees fahrenheit single response

**Outside Diameter:**

0.861 inches

**End Application:**

Aircraft, airlifter c-17a

**Connection Style:**

Swivel nut flare 1st end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded internal tube 1st end

**Features Provided:**

Nuts drilled for lockwire

**Burst Test Pressure:**

210.0 pounds per square inch

**Layer Composition And Location:**

1st layer braided corrosion resistant steel wire, partial coverage and outer layer braided corrosion resistant steel wire

**Maximum Operating Pressure:**

750.0 pounds per square inch

**Thread Size:**

0.750 inches 1st end

**Seat Angle:**

37.0 degrees 1st end

**Hydrostatic Test Pressure:**

140.0 pounds per square inch

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

21.540 inches working

**Special Features:**

Two firesleeve layers, inner layer wired in place

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Thread Series Designator:**

Unjf 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0