NSN 4720-01-420-4116

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-420-4116 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.500 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response **Outside Diameter:** 0.870 inches **Minimum Inside Bending Radius:** 7.000 inches **End Application:** 2350-01-390-4683 **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 9000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided wire and 2nd layer braided wire and outer layer molded rubber, synthetic **Maximum Operating Pressure:** 1500.0 pounds per square inch **Thread Size:** 0.750 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 3000.0 pounds per square inch

Vacuum In Torr: 50.8 **Inside Surface Condition:** Smooth **Measuring Method And Length:** 70.250 inches Media For Which Designed: Fuel/oil, hydrocarbon single response

NSN 4720-01-420-4116

Nonmetallic Hose Assembly - Page 2 of 2



Ihread	Series	Designator:
Unjf 1st	end	

.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0